

Model: CALACATTA GOLD POL.PV6 120X120(A)

Codes: 100331067

Absorption: Bla - Porcelánico ( $E \leq 0.1\%$ )



## DIMENSIONAL FEATURES

UNE-EN ISO 10545-2

|                             |             |          |
|-----------------------------|-------------|----------|
| Length                      | 1200 MM     |          |
| Thickness                   | 6 MM        |          |
| Width                       | 1200 MM     |          |
| Length and width deviation  | Below 0.15% | +/-0.3%* |
| Side straightness deviation | Below 0.15% | +/-0.3%* |
| Squareness deviation        | Below 0.15% | +/-0.3%* |
| Surface flatness deviation  | Below 0.15% | +/-0.4%* |

\*ISO-13006:2015 UNE-EN 14411:2017

## MECHANICAL FEATURES

UNE-EN ISO 10545-4-6-7-11

|                    |                  |  |
|--------------------|------------------|--|
| Breaking strenght  | 1118.5 N         |  |
| Modulus of rupture | 43.6 N/MM2       |  |
| Crack resistance   | RESISTE 3 CICLOS |  |

\*ISO-13006:2015 UNE-EN 14411:2017

## HYGIENIC FEATURES

UNE-EN ISO 10545-13-14

|                     |                |  |
|---------------------|----------------|--|
| Chemical resistance | MÍNIMO CLASE B |  |
| Stain resistance    | CLASE 5        |  |

\*ISO-13006:2015 UNE-EN 14411:2017

## ANTI-SLIP VALUE

CEN/TS 41901/02, DIN-51130 y ASTM A137.1

|                                |       |  |
|--------------------------------|-------|--|
| Slip resistance (pendulum-wet) | CL0   |  |
| Slip resistance (pendulum-dry) | >40** |  |

\*ISO-13006:2015 UNE-EN 14411:2017

## SCOPE OF USE

|                  |                              |  |
|------------------|------------------------------|--|
| Technical code-1 | Use on medium traffic floors |  |
| Technical code-2 | No additional requirements   |  |

## PACKING

|                        |                   |  |
|------------------------|-------------------|--|
| Sales units per box    | 2.880184 M2/BOX   |  |
| Sales units per pallet | 80.645161 M2/PAL  |  |
| Sales units per unit   | 1.440092 M2/PIECE |  |

System Certification

