

**Model:** OROBICO GRIGIO POL.PV6 120X120(A)

**Codes:** 100331112

**Absorption:** Bla - Porcelanico (E<=0.1%)



## DIMENSIONAL FEATURES

UNE-EN ISO 10545-2

Length	1200 MM
Width	1200 MM
Length and width deviation	Below 0.15% <span style="float: right;">+/-0.3%*</span>
Side straightness deviation	Below 0.15% <span style="float: right;">+/-0.3%*</span>
Squareness deviation	Below 0.15% <span style="float: right;">+/-0.3%*</span>
Surface flatness deviation	Below 0.15% <span style="float: right;">+/-0.4%*</span>

\*ISO-13006:2015 UNE-EN 14411:2017

## SCOPE OF USE

Technical code-1 Use on heavy traffic floors

## PACKING

Sales units per box	2.880184 M2/BOX
Sales units per pallet	80.645161 M2/PAL
Sales units per unit	1.440092 M2/PIECE

### System Certification



Do not use cleaning agents containing hydrofluoric acid.

It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint.

For big sizes, it is recommended to fix with mortars containing polymeric additives and to use the double glueing technique.

Mosaic tiles must be grouted.

This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by PORCELANOSA S.A.