

**Model:** STARK WHITE NAT. 120X270(6)(A)

**Codes:** 100332265

**Absorption:** Bla - Porcelanico (E<=0.1%)



 Sistema DAP®  
Declaración Ambiental de  
Productos de Construcción

## DIMENSIONAL FEATURES UNE-EN ISO 10545-2

Length	2700 MM	
Thickness	6 MM	
Width	1200 MM	
Length and width deviation	Below 0.15%	+/-0.3%*
Side straightness deviation	Below 0.15%	+/-0.3%*
Squareness deviation	Below 0.15%	+/-0.3%*
Surface flatness deviation	Below 0.15%	+/-0.4%*

\*ISO-13006:2015 UNE-EN 14411:2017

## MECHANICAL FEATURES UNE-EN ISO 10545-4-6-7-11

Breaking strength	>1100 N
Modulus of rupture	> 45 N/MM2
Abrasion resistance	<140

\*ISO-13006:2015 UNE-EN 14411:2017

## HYGIENIC FEATURES UNE-EN ISO 10545-13-14

Chemical resistance	MIN CLASE B
Stain resistance	5
Flammability	A1

\*ISO-13006:2015 UNE-EN 14411:2017

## ANTI-SLIP VALUE CEN/TS 41901/02, DIN-51130 y ASTM A137.1

Slip resistance (pendulum-wet)	CL1
Slip resistance (pendulum-dry)	>40

\*ISO-13006:2015 UNE-EN 14411:2017

## SCOPE OF USE

Technical code-1	Use on walls
Technical code-2	Dry interior floors

### System Certification



Do not use cleaning agents containing hydrofluoric acid.

It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint.

For big sizes, it is recommended to fix with mortars containing polymeric additives and to use the double glueing technique.

Mosaic tiles must be grouted.

This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by PORCELANOSA S.A.

## PACKING

Sales units per box 3.240441 M2/BOX

Sales units per pallet 71.289695 M2/PAL

Sales units per unit 3.240441 M2/PIECE

## ADDITIONAL NOTES

éviter les accès directs de l'extérieur si aucun dispositif de protection contre les apports abrasifs n'est prévu

## System Certification

